



# Non-Programmable Thermostats

Image	Description	Model	User Interface	Application				Power Method						Display Information		Limited Warranty	Wiring Terminals	Accessories Included	
				Stages	Gas, Oil or Electric	Heat Pump	Millivolt	Linevolt	Permanent Memory Retention	Selectable Auto or Manual Changeover	Advanced Dual Fuel Heat Pump Operation	Comfort/Economy Mode	Temperature Setpoint Limits	Display Size (Viewable)	On-Demand Backlighting				
	FocusPRO <sup>®</sup> 5000 RedLINK™ Non-Programmable	YTH5320R1116	Soft keys	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•			Battery	•	•	•	•	•	5.09 sq. in.	•	5-Year	C, R, RC, RH, W-O/B, W2-AUX/E, Y, Y2, G, L, RAS, RAS	RedLINK Internet Gateway, Equipment Interface Module, return air sensor
		YTH5320R1000	Soft keys	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•			Battery	•	•	•	•	•	5.09 sq. in.	•	5-Year	C, R, RC, RH, W-O/B, W2-AUX/E, Y, Y2, G, L, RAS, RAS	Equipment Interface Module, return air sensor
	PRO 3000 Non-Programmable	TH3110D1008	Slide switches	1 Heat/1 Cool	•		•		Dual powered (battery and hardwire)	•	Manual				1.32 sq. in.	•	5-Year	R, RC, C, W, O, B, Y, G	
		TH3210D1004	Slide switches	2Heat/1 Cool Heat Pump					Dual powered (battery and hardwire)	•	Manual				1.32 sq. in.	•	5-Year	R, C, Y, AUX, O, B, E, G, L	
	T1 Pro Non-Programmable	TH1110D2009	Soft keys	1 Heat/1 Cool – Heat Pump 1 Heat/1 Cool – Conventional	•	•	•		Dual powered (battery and hardwire)	•	Manual			•	2.37 sq. in.	•	5-Year	C, R, RC, W, O/B, Y, G	
		TH1010D2000	Soft keys	1 Heat or 1 Cool	•		•		Dual powered (battery and hardwire)	•	Manual			•	2.37 sq. in.	•	5-Year	C, R, RC, W, Y, G	
	The Digital Round™	T8775A1009	Dial	1 Heat	•				Power stealing	•					.75 sq. in.	•	5-Year	R, W	
		T8775C1005	Dial	1 Heat/1 Cool	•				Power stealing	•	Manual				.75 sq. in.	•	5-Year	R, RC, C, W, O, B, Y, G	
	The Round™	T87K1007	Dial	1 Heat or 1 Cool	•				Battery assisted power stealing					50010944-001	N/A		5-Year	R, W, Y	
		T87N1000	Dial	1 Heat/1 Cool	•				Battery assisted power stealing		Manual			50010944-001	N/A		5-Year	R, RC, W, Y, G, O, B	
		T87N1026	Easy-To-See™	1 Heat/1 Cool	•				Battery assisted power stealing		Manual			50010944-001	N/A		5-Year	R, RC, W, Y, G, O, B	
		T834N1002 Vertical	Slide switches and lever	1 Heat/1 Cool	•				Mechanical		Manual			50019661-001	N/A		5-Year	R, RC, W, Y, G, O, B	
		T8034N1007 Horizontal	Slide switches and lever	1 Heat/1 Cool	•				Mechanical		Manual			50019661-001	N/A		5-Year	R, RC, W, Y, G, O, B	
		T822K1000	Slide switches and lever	1 Heat	•				Mechanical		Positive off			50019661-001	N/A		5-Year	R, W	
		T822K1018	Slide switches and lever	1 Heat	•				Mechanical					50019661-001	N/A		5-Year	R, W	
		T827K1009	Slide switches and lever	1 Heat	•		•		Mechanical			Positive off			50019661-001	N/A		5-Year	R, W
		TL7235A1003	Horizontal lays	1 Heat				•	208/240 V						2.67 sq. in.	•	5-Year	4 wire DPST	
		TL7230A1004	Dial	1 Heat				•	208/240 V						N/A		5-Year	DPST	
		T410/T4398	Dial	1 Heat				•	120/208/240/277 V						N/A		1-Year	SPST or DPST	